

PFP-6HP-FL

FLOATING PUMP

This high volume Kawasaki powered floating pump is the most efficient on the market. It gives you the highest volume in its range.



ENGINE SPECIFICATIONS

- FJ180V Kawasaki air cooled engine
- Single cylinder, 4-stroke gasoline engine
- Manual recoil start
- 0.3 gallon (1.8 l) integrated fuel tank


PUMP UNIT SPECIFICATIONS

- Direct drive C.E.T. single stage centrifugal pump
- Pump body made from resistant aluminum alloy
- Aluminum impeller
- Self priming system
- Need only 1" deep of water
- One 2 1/2" (65 mm) delivery outlet
- One 3" (77 mm) suction inlet
- Light weight heavy duty floater
- Detachable floater
- Dimensions:
 - Length: 35" (794 mm)
 - Width: 25 1/2" (648 mm);
 - Height: 19" (482 mm)
- Weight: 64 lbs (29 kg)

PERFORMANCE

200 GPM @ 5 PSI
170 GPM @ 10 PSI

105 GPM @ 20 PSI
50 GPM @ 30 PSI



LIMITED WARRANTY

- 3 YEARS



ACCEPT ONLY THE BEST



**A CENTURY
OF ENGINEERING
FOR THE BRAVEST**

75 Hector St., P.O. Box 90,
Pierreville (Québec)
Canada J0G 1J0
Phone : 1-800-567-2719
Fax : 1-800-434-2613
www.fire-pumps.com